

LDIinteriors™

Sustainable Technology • Limitless Color • Ultimate Performance

Typical Physical Properties

REVIVE

TEST	UNITS	METHODS	RESULTS
Width	inches (cm)	ASTM D-1776	54 (137)
Thickness	inches (mm)	ASTM D-1776	0.046 (1.17)
Weight	O/yd2 (g/m2)	ASTM D-3776	21.4 (725.58)
Abrasion #10 Duck Cloth	Double Rubs	Wyzenbeek ASTM D-3597	500,000*
Crocking	AATCC Scale	AATCC-8	5 dry 5 wet (water) 5 wet (alcohol)
Flammability		IMO FTPC Part 8	PASS
		CA TB117-2013 Section 1	PASS
		ASTM E-84	CLASS A
Colorfastness	Light	AATCC-16.3	CLASS 5
VOC Emissions		California 01350	PASS
Hydrolytic Stability		ISO 1419 Method C	PASS

Content: 50% Silicone, 50% Polyester

Disinfecting/Cleaning Information

Cleaning Code: WS

Visit www.Ldiinteriors.com for complete cleaning instructions and a list of cleaners and disinfectants that we have tested.



*ACT Registered Certification Marks

*Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan